



Document No.: NMS 688/2 Rev C, September 26, 2016

NCAMP Material Specification

This specification is generated and maintained in accordance with NCAMP
Standard Operating Procedures, NSP 100

265°F Vacuum Bag Cure, Epoxy Prepregs, Type 42, Class 2, Grade 193, Style
12K-193- SFP-OSI
(TenCate Advanced Composites USA, Inc. TCAC12k HTS SFP OSI/TC250)

Prepared by: Yeow Ng, John Tomblin, David Ostrodka, Vinsensius Tanoto

Reviewed by: Barry Meyers (TenCate), Royal Lovingfoss (NCAMP)

This specification is intended for general distribution to the public, either freely or at a price that does not exceed the cost of reproduction (e.g. printing) and distribution (e.g. postage).

National Center for Advanced Materials Performance
Wichita State University – NIAR
1845 Fairmount Ave., Wichita, KS 67260-0093, USA

3.5.3 Cured Laminate Mechanical Properties:

TABLE 5 - Required Cured Laminate Tests for Mechanical Properties (Class 2)

Property	Test Method ⁽¹⁾	Requirements ⁽³⁾
0° (warp) Tension Strength and Modulus, Room Temperature, Ambient Layup: [0] ₁₂	Strength ⁽²⁾ : Min. Ind.	

QUALIFIED PRODUCTS LIST

Supplier Product Designation	Supplier Name and Production Location	Date Qualified	Specification Callout ⁽¹⁾
TCAC12k HTS SFP OSI/TC250 TCAC#50123988	Supplier Name: TenCate Advanced Composites USA, Inc. Production Location: 18410 Butterfield Blvd. Morgan Hill, CA 95037 USA	September 2016	NMS 688/2 Classification callout is optional because Type 42, Class 2, Grade 193, Style 12K- 193-SFP-OSI is the only classification allowed c0v t